

APRON VARIABLE HEIGHT SLOT DRAIN TABLE 330" RUN (FG ELEV. 1419.04)								
2 EA. 330LF @ 0.52% DURASLOT OR EQUAL VARIABLE HEIGHT STA. 2+91.5 TO STA. 6+21.5, 105.0' LT & 105.0' RT								
PER 10' PIPE SECTION W/ GRATES, END CAP, COUPLER BANDS, ADAPTOES TO N-12 & ALL HARDWARE								
DURASLOT	H-1		H-2	PIPE DIA.	FG	START	INV. ELEV.	INV PIPE'
NUMBER	H-1	H-2				START	END	INV. ELEV. END
18-V13	10.000	10.625	18	1419.04	2.333	1416.71	2.385	1416.65
18-V14	10.625	11.250	18	1419.04	2.385	1416.65	2.438	1416.60
18-V15	11.250	11.875	18	1419.04	2.438	1416.60	2.490	1416.55
18-V16	11.875	12.500	18	1419.04	2.490	1416.55	2.542	1416.50
18-V17	12.500	13.125	18	1419.04	2.542	1416.50	2.594	1416.45
18-V18	13.125	13.750	18	1419.04	2.594	1416.45	2.646	1416.39
18-V19	13.750	14.375	18	1419.04	2.646	1416.39	2.698	1416.34
18-V20	14.375	15.000	18	1419.04	2.698	1416.34	2.750	1416.29
18-V21	15.000	15.625	18	1419.04	2.750	1416.29	2.802	1416.24
18-V22	15.625	16.250	18	1419.04	2.802	1416.24	2.854	1416.19
18-V23	16.250	16.875	18	1419.04	2.854	1416.19	2.906	1416.13
18-V24	16.875	17.500	18	1419.04	2.906	1416.13	2.958	1416.08
18-V25	17.500	18.125	18	1419.04	2.958	1416.08	3.010	1416.03
18-V26	18.125	18.750	18	1419.04	3.010	1416.03	3.063	1415.98
18-V27	18.750	19.375	18	1419.04	3.063	1415.98	3.115	1415.93
18-V28	19.375	20.000	18	1419.04	3.115	1415.93	3.167	1415.87
18-V29	20.000	20.625	18	1419.04	3.167	1415.87	3.219	1415.82
18-V30	20.625	21.250	18	1419.04	3.219	1415.82	3.271	1415.77
18-V31	21.250	21.875	18	1419.04	3.271	1415.77	3.323	1415.72
18-V32	21.875	22.500	18	1419.04	3.323	1415.72	3.375	1415.67
18-V33	22.500	23.125	18	1419.04	3.375	1415.67	3.427	1415.61
18-V34	23.125	23.750	18	1419.04	3.427	1415.61	3.479	1415.56
18-V35	23.750	24.375	18	1419.04	3.479	1415.56	3.531	1415.51
18-V36	24.375	25.000	18	1419.04	3.531	1415.51	3.583	1415.46
18-V37	25.000	25.625	18	1419.04	3.583	1415.46	3.635	1415.40
18-V38	25.625	26.250	18	1419.04	3.635	1415.40	3.688	1415.35
18-V39	26.250	26.875	18	1419.04	3.688	1415.35	3.740	1415.30
18-V40	26.875	27.500	18	1419.04	3.740	1415.30	3.792	1415.25
18-V41	27.500	28.125	18	1419.04	3.792	1415.25	3.844	1415.20
18-V42	28.125	28.750	18	1419.04	3.844	1415.20	3.896	1415.14
18-V43	28.750	29.375	18	1419.04	3.896	1415.14	3.948	1415.09
18-V44	29.375	30.000	18	1419.04	3.948	1415.09	4.000	1415.04
18-V45	30.000	30.625	18	1419.04	4.000	1415.04	4.052	1414.99
DURASLOT OR APPROVED EQUAL								



N.T.S.



N.T.S



NTS

NOTE:
THE CONTRACTOR SHALL FORM THE P.C.C. TO PROVIDE A VERTICAL FACE AFTER
PLACEMENT OF ASPHALT, THE CONTRACTOR SHALL SAW AND SEAL, AS SHOWN.



N.T.S.

NOTES:

1. BASKET MUST BE FIRMLY ATTACHED TO EXISTING OR NEW BASE PRIOR TO PLACING PCC.
2. ALL WIRE SIZES SHOWN ARE MINIMUM SIZE.
3. DOWELS SHALL BE HELD FIRMLY IN THE ABOVE WELDED ASSEMBLY.
4. ANY PAVEMENT SHOWN WITH THICKENED EDGE WILL BE PAID AS NOMINAL THICKNESS (").
5. THE TOLERANCE FOR DOWEL ALIGNMENT IN EITHER HORIZONTAL OR VERTICAL PLANE IS 1/4"/FT.
6. DOWEL BARS SHALL BE EVENLY SPACED ACROSS EACH PANEL WITH NO BAR BEING LESS THAN ONE FOOT FROM THE PANEL EDGE.

BID DOCUMENTS